

# SR320~SR3200

## 3.0Amp Schottky Barrier Rectifiers




### Features

The plastic package carries Underwriters Laboratory Flammability Classification 94V-0  
 Metal silicon junction, majority carrier conduction  
 Low power loss, high efficiency  
 High forward surge current capability  
 High temperature soldering guaranteed:  
 250°C/10 seconds, 0.375" (9.5mm) lead length,  
 5 lbs. (2.3kg) tension

### Mechanical Data

**Case:** JEDEC DO-27 molded plastic body  
**Terminals:** Plated axial leads, solderable per MIL-STD-750, Method 2026  
**Polarity:** Color band denotes cathode end  
**Mounting Position:** Any  
**Weight:** 0.04 ounce, 1.10 grams

### DO-201AD(DO-27)



Dimensions in inches and (millimeters)

### Maximum Ratings And Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified. Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

	SYMBOLS	SR 320	SR 330	SR 340	SR 350	SR 360	SR 370	SR 380	SR 390	SR 3100	SR 3150	SR 3200	UNITS	
Maximum repetitive peak reverse voltage	$V_{RRM}$	20	30	40	50	60	70	80	90	100	150	200	VOLTS	
Maximum RMS voltage	$V_{RMS}$	14	21	28	35	42	49	56	63	70	105	140	VOLTS	
Maximum DC blocking voltage	$V_{DC}$	20	30	40	50	60	70	80	90	100	150	200	VOLTS	
Maximum average forward rectified current 0.375" (9.5mm) lead length(see fig.1)	$I_{AV}$	3.0											Amps	
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	$I_{FSM}$	80.0											Amps	
Maximum instantaneous forward voltage at 3.0A	$V_F$	0.55		0.70		0.85			0.95			Volts		
Maximum DC reverse current at rated DC blocking voltage	$I_R$	0.5						0.2			mA			
$T_A=25^{\circ}C$ $T_A=100^{\circ}C$		20.0			10.0			2.0						
Typical junction capacitance (NOTE 1)	$C_J$	250			160									pF
Typical thermal resistance (NOTE 2)	$R_{\theta JA}$	40.0											°C/W	
Operating junction temperature range	$T_J$	-65 to +125						-65 to +150						°C
Storage temperature range	$T_{STG}$	-65 to +150											°C	

**Note:** 1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.

2. Thermal resistance from junction to ambient at 0.375" (9.5mm) lead length, P.C.B. mounted

### Ratings And Characteristic Curves

FIG. 1- FORWARD CURRENT DERATING CURVE




FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4-TYPICAL REVERSE CHARACTERISTICS




FIG. 5-TYPICAL JUNCTION CAPACITANCE




FIG. 6-TYPICAL TRANSIENT THERMAL IMPEDANCE

